

PGDQ2.MH46287

Marking and Labeling Systems - Component

Page Bottom

Marking and Labeling Systems - Component

See General Information for Marking and Labeling Systems - Component

SHANGHAI PRAMERS CHEMI-TECH CO LTD

MH46287

858 BAOYUAN SIXTH RD

JIADING

201812 SHANGHAI, CHINA

Printed labels:

Model No.	Application Surface	Max Temp (C)	Min Temp (C)	Indoor Use	Outdoor Use	Additional Conditions
"PLM72826", "PLM72825"						
	Acrylic paint (AC PT)	150	-40	X	-	-
	Aluminum (AL)	150	-40	X	-	-
	Epoxy paint (EP PT)	150	-40	X	-	-
	Galvanized steel (GS)	150	-40	X	-	-
	Porcelain (PRCLN)	150	-40	X	-	-
	Stainless steel (SS)	150	-40	X	-	-
	Alkyd paint (AK PT)	100	-40	X	-	-
	Melamine (ME)	100	-40	X	-	-
	Nylon - polyamide (PA)	100	-40	X	-	-
	Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
	Polyester paint (PER PT)	100	-40	X	-	-
	Unsaturated polyester - thermoset (UP)	100	-40	X	-	-
	Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
	Polycarbonate (PC)	80	-40	X	-	-
	Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
	Polystyrene (PS)	80	-40	X	-	-
	Alkyd Painted Plastic	60	-40	X	-	-
	Polyethylene (PE)	60	-	X	-	-
"PLM7380"						
	Acrylic paint (AC PT)	125	-40	X	-	-
	Alkyd paint (AK PT)	125	-40	X	-	-
	Aluminum (AL)	125	-40	X	-	-
	Epoxy paint (EP PT)	125	-40	X	-	-

Galvanized steel (GS)	125	-40	X	-	-
Polyester paint (PER PT)	125	-40	X	-	-
Stainless steel (SS)	125	-40	X	-	-
Nylon - polyamide (PA)	100	-40	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polycarbonate (PC)	100	-40	X	-	-
Polypropylene (PP)	80	-40	X	-	-
Polystyrene (PS)	80	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	60	-40	X	-	-

"PLM7815", "PLM7818"

Acrylic paint (AC PT)	125	-40	X	-	-
Alkyd paint (AK PT)	125	-40	X	-	-
Aluminum (AL)	125	-40	X	-	-
Epoxy paint (EP PT)	125	-40	X	-	-
Galvanized steel (GS)	125	-40	X	-	-
Polyester paint (PER PT)	125	-40	X	-	-
Polyethylene terephthalate (PET)	125	-40	X	-	-
Porcelain (PRCLN)	125	-40	X	-	-
Stainless steel (SS)	125	-40	X	-	-
Nylon - polyamide (PA)	100	-40	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polybutylene terephthalate (PBT)	100	-40	X	-	-
Polycarbonate (PC)	100	-40	X	-	-
Polyphenylene sulfide (PPS)	100	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-	X	-	-
Polystyrene (PS)	80	-40	X	-	-

"PLM7816", "PLM7875"

Acrylic paint (AC PT)	150	-40	X	-	-
Alkyd paint (AK PT)	150	-40	X	-	-
Aluminum (AL)	150	-40	X	-	-
Epoxy paint (EP PT)	150	-40	X	-	-
Galvanized steel (GS)	150	-40	X	-	-
Polyester paint (PER PT)	150	-40	X	-	-
Polyethylene terephthalate (PET)	150	-40	X	-	-
Porcelain (PRCLN)	150	-40	X	-	-
Stainless steel (SS)	150	-40	X	-	-
Nylon - polyamide (PA)	100	-40	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-

Polybutylene terephthalate (PBT)	100	-40	X	-	-
Polycarbonate (PC)	100	-40	X	-	-
Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-	X	-	-
Polystyrene (PS)	80	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	60	-40	X	-	-

"PLM7840TL"

Acrylic paint (AC PT)	150	-40	X	-	-
Alkyd paint (AK PT)	150	-40	X	-	-
Aluminum (AL)	150	-40	X	-	-
Epoxy paint (EP PT)	150	-40	X	-	-
Galvanized steel (GS)	150	-40	X	-	-
Polyester paint (PER PT)	150	-40	X	-	-
Polyethylene terephthalate (PET)	150	-40	X	-	-
Porcelain (PRCLN)	150	-40	X	-	-
Stainless steel (SS)	150	-40	X	-	-
Nylon - polyamide (PA)	100	-40	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polybutylene terephthalate (PBT)	100	-40	X	-	-
Polycarbonate (PC)	100	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-	X	-	-
Polystyrene (PS)	80	-40	X	-	-

"PLM7860"

Acrylic paint (AC PT)	150	-40	X	-	-
Alkyd paint (AK PT)	150	-40	X	-	-
Aluminum (AL)	150	-40	X	-	-
Epoxy paint (EP PT)	150	-40	X	-	-
Galvanized steel (GS)	150	-40	X	-	-
Polyester paint (PER PT)	150	-40	X	-	-
Stainless steel (SS)	150	-40	X	-	-
Nylon - polyamide (PA)	100	-	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polycarbonate (PC)	100	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	80	-40	X	-	-
Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-	X	-	-
Polystyrene (PS)	80	-40	X	-	-

"PLM7871", "PLM7872"

--	--	--	--	--	--

Acrylic paint (AC PT)	150	-40	X	-	-
Acrylic powder paint (AC PDR PT)	150	-40	X	-	-
Alkyd paint (AK PT)	150	-40	X	-	-
Aluminum (AL)	150	-40	X	-	-
Epoxy paint (EP PT)	150	-40	X	-	-
Epoxy powder paint (EP PDR PT)	150	-40	X	-	-
Epoxy/polyester powder paint	150	-40	X	-	-
Galvanized steel (GS)	150	-40	X	-	-
Polyester paint (PER PT)	150	-40	X	-	-
Polyester powder paint (PER PDR PT)	150	-40	X	-	-
Polyethylene terephthalate (PET)	150	-40	X	-	-
Porcelain (PRCLN)	150	-40	X	-	-
Stainless steel (SS)	150	-40	X	-	-
Textured epoxy powder paint	150	-40	X	-	-
Textured epoxy/polyester powder paint	150	-40	X	-	-
Textured polyester powder paint	150	-40	X	-	-
Urethane powder paint	150	-40	X	-	-
Nylon - polyamide (PA)	100	-40	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polycarbonate (PC)	100	-	X	-	-
Zinc plated metal with chromate post treatment	100	-	X	-	-
Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-40	X	-	-
Polystyrene (PS)	80	-40	X	-	-
Teflon coated metal	80	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	60	-40	X	-	-
Polyvinyl chloride (PVC)	60	-40	X	-	-

"PLM7883"

Acrylic paint (AC PT)	125	-40	X	-	-
Alkyd paint (AK PT)	125	-40	X	-	-
Aluminum (AL)	125	-40	X	-	-
Epoxy paint (EP PT)	125	-40	X	-	-
Galvanized steel (GS)	125	-40	X	-	-
Polyester paint (PER PT)	125	-40	X	-	-
Porcelain (PRCLN)	125	-40	X	-	-
Stainless steel (SS)	125	-40	X	-	-
Nylon - polyamide (PA)	100	-	X	-	-
Phenolic - Phenol Formaldehyde (PH)	100	-40	X	-	-
Polycarbonate (PC)	100	-	X	-	-

Polyphenylene oxide/ether (PPOX)	80	-40	X	-	-
Polypropylene (PP)	80	-	X	-	-
Polystyrene (PS)	80	-40	X	-	-
Acrylonitrile butadiene styrene (ABS)	60	-40	X	-	-

Marking: Company name and model designation.

Last Updated on 2008-03-26

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright ?2009 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

